

CIRCULAR SAW

LINDOVA CS3

Pneumatic circular saw for thin sheet, steel plate and aluminium.

Lindova CS3 is an air hydraulic circular saw with an adjustable cutting depth of up to 10 mm. Sawing can be carried out from the centre of the plate surface. A guide groove is positioned on the front of the tool, which makes it easy to cut in a straight line.


CS3 is supplied as standard with a 45 mm blade for thin sheet. Three 50 mm blades designed for use with thin sheet, steel plate and aluminium, respectively, are also available as separate accessories.

Efficient damping and small tolerances for all components minimize the vibrations and ensure a high level of operational reliability.

The function handle is fitted with safety guards. There is also a plastic hood over the saw head which insulates the head against the chill from the hydraulic air, amongst other things.

And because we both design and manufacture the CS3 Circular Saw ourselves, we can guarantee both a complete stock of spare parts and rapid service when required.

CS3 CIRCULAR SAW

Revs.	3000 rpm	Min. hose	8 mm
Air consumption	7.5 l/s	Connection	R 1/4
Length	245 mm	Art. nr.	8440
Weight	1.4 kg		
Cutting dept	7.5 mm with 45 mm blade 10.0 mm with 50 mm blade	Vibration level:	< 2.5 m/s ²
		Noise level:	80 dB (A) 

SAW BLADES

Type	No. teeth	Diameter	Designed for	Art. no.
Fine	84	45 mm	Thin sheet	1863-80*
Fine	92	50 mm	Thin sheet	1931-92
Medium	62	50 mm	Steel plate	1931-62
Coarse	34	50 mm	Aluminium	1931-34

* Supplied as standard



Postal address:
Lindova AB, Box 39, 711 21 Lindesberg, Sweden
Office: **Stafettgatan 1, Lindesberg, Sweden**
Tel: + 46 581 886 50 Fax: + 46 581 886 59
Web site: www.lindova.se
E-mail: info@lindova.se